

Upload Date	Change Note	Version
2015-01-21	<p>The function stabilization in Serial Configuration mode</p> <ul style="list-style-type: none"> - When user entered into Serial configuration mode by S/W Trigger and has set new configuration, sometimes, it will not take effect right after new configuration set. This problem is fixed. - When user entered into Serial configuration mode by H/W Trigger and has read configuration value, sometimes, some parts of MAC address is not displayed. This problem is fixed. 	5.11
2014-01-14	<p>Stabilizing the Flash</p> <p>Fixed the Search error at the DHCP or DNS fail</p> <p>RTS Timing Change : After transmitting the data, RTS signal is reversed after waiting 3 clocks.</p>	5.10
2013-11-21	Adjusted RTS/CTS Timing	4.32
2013-01-30	<p>Removed the DNS IP filtering.</p> <p>Applied the stable codes.</p>	4.31
2012-04-03	<p>Add MAC, IP address Gateway IP address and Subnet IP address output when Debug message enabled.</p> <p>Sending 1byte dummy data to gateway during booting in order to update ARP table.</p> <p>Serial command mode of H/W trigger revised.</p> <p>Initializing configuration socket again after DNS query.</p> <p>Initializing configuration socket again after DHCP routine.</p>	4.10
2012-04-03	Legacy versions package (old version)	